




MATERIAL SAFETY DATA SHEET

NFPA Designation 704
 DEGREE OF HAZARD
 4 = EXTREME
 3 = HIGH
 2 = MODERATE
 1 = SLIGHT
 0 = INSIGNIFICANT



May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910, 1200. Standard must be consulted for specific requirements.

U.S. DEPARTMENT OF LABOR Occupational Safety and Health Administration (Non-Mandatory Form) Form-Approved OMB No. 1218.0072

CHEMICAL NAME**Woodcraft®****PRODUCT USAGE**

Smoke Damaged Wood Restoring Gel

SECTION I

Manufacturer: II-Rep-Z	Emergency Telephone Number: (412) 351-8686
Address: 1135 Braddock Avenue	Telephone Number For Information: (412) 351-8686
City, State, Zip: Braddock, PA 15104	Date Prepared: March 1, 1999 Updated: July 22, 2004

SECTION II - Hazardous Ingredient Information

Hazardous Components (If component is non-hazardous, specify by * designation) (Specific Chemical Identity: CAS#)	% optional
Isoparaffinic Hydrocarbon Iso-Par (C.A.S. #64742-48-9)	27%
*P.E.G. Lanolin (C.A.S. #8039-09-6)	2%
*Blandol White Mineral Oil (C.A.S. Mixture)	3%
*Alkoxylated Alkylphenol Iconol (C.A.S. # 9036-19-5)	3%
*Amine Alkylbenzene Sulfonate (C.A.S. # 1045-07-1)	7%
*Tall Oil Fatty Acid Acintol (C.A.S. # 61790-12-3)	6%
*Alkonolamines Monoethanolamine (C.A.S. # 141-18-5)	1%
*Water (C.A.S.# 7732-18-5)	51%
*Fragrance Citrus (G,R,A.S.)	
*Parachlorometaxyleneol (PCMX) (G.R.A.S.)	
*Fluoresceine "O" (G.R.A.S.)	

SECTION III - Physical/Chemical Characteristics

Boiling Point	Over 196°F	Specific Gravity (H ₂ O = 1)	1.030
Vapor Pressure (mm Hg.)	N.A.	Melting Point	N.A.
Vapor Density (Air=1)	N.A.	Evaporation Rate (Butyl Acetate=1)	N.A.
Solubility Rate	100%	Percent, Volatile by Volume (%)	N.A.
Appearance and Odor	Golden Gree, Citrus Fragrance		

SECTION IV - Fire and Explosion

Flash Point (Method Used)	>300°F	Flammable Limits	N.A.	LEL	N.A.	UEL	N.A.
Extinguishing Media	water, mist, foam, chemical						
Special Fire Fighting Procedures	None. This product will neither support or be the source of any fire.						
Unusual Explosion Hazard	None						

Reproduce Locally

OSHA 174 Equivalent, Sept. 1985

SECTION V - Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	Avoid freezing or extreme heat

Incompatibility (Materials to Avoid)

None

Hazardous Decomposition or by-Products

Under fire conditions - oxide of carbon, nitrogen, sulfur

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

SECTION VI - Health Hazard Data

Health Hazards (Acute and Chronic): Route(s) of Entry/Signs and Symptoms of Exposure

Eyes, skin, and ingestion are the routes of entry. May cause burns to eyes. In concentrated form - may cause slight irritation to the skin .

Emergency and First Aid Procedures

In case of eye contact, flush with water for 10-15 minutes. If irritation persists, consult a physician. In case of skin irritation due to prolonged contact with concentrate, flush with water for 10 minutes. Apply moisturizing lotion if needed. Remove any contaminated clothing. In case of ingestion, give large quantities of water to dilute. Do not induce vomiting. Immediately get medical attention. .

Carcinogenicity: NIP? IARC Monographs? OSHA Regulated?

Unknown

Medical Conditions Generally Aggravated by Exposure

Unknown

SECTION VII - Precautions For Safe Handling And Use

Steps to be taken in Case Material is Released or Spilled

Contain spill. mop or sweep smaller spills for re-use or disposal. Use non-slip shoes or boots-slippery

Waste Disposal Method

Small diluted solutions may flush to sanitary sewer. Check all local, state, provincial, and federal regulations.

Precautions To Be Taken In Handling And Storing

Keep out of reach of children. Very slippery. Protect from freezing..

Other Precautions

Keep out of reach of children.

SECTION VIII - Control Measures

Respiratory Protection (Specific Type)

None

Ventilation	Local Exhaust	X	Special	N.A.
	Mechanical (General)	X	Other	N.A.

Protection Gloves

Recommended

Eye Protection

Splash goggles

Other Protective Clothing or Equipment

none

Work/Hygienic Practices

Keep tightly sealed.

To the best of our knowledge, the information contained herein is accurate. However, neither Unsmoke Systems, its suppliers, nor its distributors assumes any liability whatsoever for the accuracy or completeness of the information. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards may be described herein, we cannot guarantee that these are the only hazards which exist. Information herein is given in good faith, but no warranty, expressed or implied, is made.